

ANSI D-RING COBRA® PRO STYLE

25 mm

Art.no.: FX25KVD



This innovative component is a synergistic hybrid of two standard components of safety industry hardware: the stainless-steel d-ring and the ANSI COBRA® PRO STYLE - a buckle which meets the highest safety requirements for its users. Its unique construction prevents the D-Ring from getting squeezed against the webbing and therefore guarantees easy handling.

The ANSI COBRA® PRO STYLE, certified according to the American safety standard ANSI, is thicker and even stronger than the COBRA® PRO STYLE. This buckle is marked according to the ANSI norm with a guaranteed tensile strength of 15 kN. However, we guarantee 18 kN for the buckle and 22 kN for the d-ring and point this out in the technical specifications accordingly. Certified according to ANSI/ASSE and upon request NFPA.

use cases:

PPE, Fashion, air sports, tactical, equipment

Technical specifications

BODY	Material: aluminium Color: black Finish: ktl coated
CLIPS	Material: brass Color: colorless Finish: polished
BAR	Material: stainless steel Color: colorless Finish: polished
D-RING	Material: stainless steel Color: colorless Finish: polished
BREAKING LOAD TENSILE STRENGTH	18 kN
BREAKING LOAD D-RING	22 kN

WEIGHT	120 g
RECOMM. WEBBING WIDTH MALE PART	25 mm
RECOMM. WEBBING WIDTH FEMALE PART	25 mm
OUTER DIMENSION LENGTH	67 mm
OUTER DIMENSION WIDTH	48 mm
OUTER DIMENSION DEPTH	14 mm
TECHNICAL DESIGN MALE PART	adjustable
TECHNICAL DESIGN FEMALE PART	non adjustable with integrated D-ring
SINGLE PIECE TESTED	Yes
COUNTRY OF ORIGIN	Austria
 Patented	
STANDARDS	ANSI/ASSE Z359.12-2019, CSA Z259.12-2016 Class I, EN358:2018-11 (partial)
	

